

There's more
 to smart than before!

Truly Eco Friendly & Energy Saving

LED Light



TERMS & CONDITIONS :

- All Items will be Supplied in Standard packing only.
- Product images are for illustrative purposes only and may differ from the actual product
- All disputes subject to Delhi jurisdiction

Klick Electrical Industries Unit-II

62, Rama Road, Industrial Area,
 New Delhi -110015
 Customer care - 9811385356
 Email ID : klick_cables@yahoo.com
 Website : www.klickelectricals.in

DEALER / DISTRIBUTOR



- RESIDENTIAL
- INDUSTRIAL
- COMMERCIAL
- OUTDOOR



Items	Page No.
Glamour LED Slim Panel Light (Alum.)	02
Glamour LED Surface Panel Light (Alum.)	03
Spectra LED Panel (PC)	04
Spectra LED Surface Ring (PC)	05
Deep Junction LED Light	06
Down LED Light	07-08
Down LED Light Striker & Sky Spot Light	09
Vista COB Down Light	10
Phantom LED Surface Light	11
Track LED Light	12
Nova T-Bulb	13
Aristo Plus Tube Light	14
Victor LED Bulb	15
Venus AC/DC Bulb & Emergency Tube Light	16
Flora Slim Flood Light	17-18
Maxx Plus LED Street Light	19
High Bay Light	20
Outdoor Garden Lights	21



WHO WE ARE..?

Klick offers is home to a wide variety of energy efficient lighting solutions with hand-crafted perfection. Our energy efficient and eccentric spectrum lighting products provide extraordinary effects and avoid hefty bills. Our aim is to understand and fulfil your lighting needs with our state of the art lighting products and move a step closer to achieving affordable lighting across India. Klick envisions to be a part of your day to day life by offering advanced lighting solutions ranging from residential, commercial to outdoor. Our RoHS-compliant products are designed to protect homes and lives from electrical risks. This allows KLICK to focus on its main goal of developing energy-efficient lighting solutions while also lowering customers' energy bills and decreasing environmental impact. Discover the future of lighting with us.

Applications

Supermarkets & Shopping Malls, Hotel Lighting, Office & School, Garden Lamp, Home Decor Lights



LED for more comfortable Lights



Glamour LED Slim Panel (Aluminium)



Product Specification

Product Code	KL 01	KL 02	KL 03
Input Power	8w	15w	22w
Length/Dia	120mm	170mm	225mm
Breath	120mm	170mm	225mm
Height	25mm	25mm	25mm
Cut Out	100mm	150mm	200mm
Lumens	≥800	≥1500	≥2200
Input Voltage	110-300V AC 50Hz		
Power Factor	0.95		
Colour Temperature	2700K-6500K		
CRI	≥85		
Beam Angle	120°		
Operating Temperature	{-20 to +60°C}		

Glamour LED Surface Panel (Aluminium)



Product Specification

Product Code	KL 04	KL 05	KL 06
Input Power	8w	15w	22w
Length/Dia	120mm	170mm	225mm
Breath	120mm	170mm	225mm
Height	35mm	35mm	38mm
Cut Out	100mm	150mm	200mm
Lumens	≥800	≥1500	≥2200
Input Voltage	110-300V AC 50Hz		
Power Factor	0.95		
Colour Temperature	2700K-6500K		
CRI	≥85		
Beam Angle	120°		
Operating Temperature	{-20 to +60°C}		

Spectra LED Panel (PC)



Product Specification

Product Code	KL 07	KL 08	KL 09	KL 10
Input Power	4w	8w	15w	22w
Outer Size	70mm	115mm	165mm	220mm
Cut Out	90mm	100mm	150mm	90mm
Height	40mm	40mm	40mm	200mm
Lumens	≥400	≥800	≥1500	≥2200
Input Voltage	110-300V AC 50Hz			
Power Factor	0.95			
Colour Temperature	2700K-6500K			
CRI	≥85			
Beam Angle	120°			
Operating Temperature	{-20 to +60°C}			

Spectra Surface Ring (PC)



Product Specification

Product Code	KL 11	KL 12	KL 13	KL 14
Input Power	4w	8w	15w	22w
Outer Size	70mm	115mm	165mm	220mm
Cut Out	90mm	100mm	150mm	90mm
Height	40mm	40mm	40mm	200mm

Deep Junction LED Lights



Product Specification

Product Code	KL 15	KL 16	KL 17	KL 18
Input Power	3w Hexa	6w Hexa	6w Aura	16w Aura
Outer Size	80mm	115mm	80mm	135mm
Cut Out	45mm	80mm	45mm	45mm
Height	45mm	72mm	60mm	70mm
Lumens	≥300	≥600	≥600	≥1600
Input Voltage	110-300V AC 50Hz			
Power Factor	0.95			
Colour Temperature	2700K-6500K			
CRI	≥85			
Beam Angle	45°-120°			
Operating Temperature	{-20 to +60°C}			

Down LED Light



Product Specification

Product Code	KL 19	KL 20	KL 21	KL 22
Input Power	7w Liva Plus	6w Euro	3w Crysta	6w Crysto
Outer Size	110mm	110mm	80mm	110mm
Cutout Size	70mm	70mm	45mm	70mm
Height	45mm	45mm	45mm	45mm
Lumens	≥700	≥600	≥300	≥700
Input Voltage	110-300V AC 50Hz			
Power Factor	0.95			
Colour Temperature	2700K-6500K			
CRI	≥85			
Beam Angle	60°			
Operating Temperature	{-20 to +60°C}			

Down LED Lights



Product Specification

Product Code	KL 23	KL 24	KL 25
Input Power	9w Bolt	6w Blaze	6w Flare
Outer Size	110mm	90mm	90mm
Cutout Size	70mm	74mm	74mm
Height	40mm	22mm	22mm
Lumens	≥900	≥600	≥600
Input Voltage	110-280V AC 50Hz		
Power Factor	0.95		
Colour Temperature	2700K-6500K		
CRI	≥85		
Beam Angle	40°		
Operating Temperature	{-20 to +60°C}		

Down LED Light Striker & Sky Spot Light



Product Specification

Product Code	KL 26	KL 27	KL 28	KL 29
Input Power	3w Stricker	5w Stricker	5w Stricker Plus	2w Sky
Outer Size	68mm	68mm	61mm	-
Cutout Size	68mm	68mm	61mm	-
Height	13mm	13mm	150mm	-
Lumens	≥300	≥500	≥300	≥200
Input Voltage	110-300V AC 50Hz			
Power Factor	0.95			
Colour Temperature	2700K-6500K			
CRI	≥85			
Beam Angle	60° / 40°			
Operating Temperature	{-20 to +60°C}			

Vista COB Down Light



Product Specification

Product Code	KL 30	KL 31	KL 32
Input Power	7w	12w	15w
Outer Size	115mm	145mm	180mm
Cutout Size	95mm	130mm	160mm
Height	65mm	85mm	95mm
Lumens	≥1000	≥2000	≥3000
Beam Angle	30°	30°	30°
Input Voltage	110-300V AC 50Hz		
Power Factor	0.95		
Colour Temperature	3000K-4000K-6500K		
CRI	≥85%		
Protections	Surge upto 2.5 KV True-Isolated		

Phantom LED Surface



Product Specification

Product Code	KL 33	KL 34
Input Power	6w	15w
Outer Size	80mm	135mm
Height	40mm	40mm
Lumens	≥600	≥1500
Input Voltage	85-280V AC 50Hz	
Power Factor	0.95	
Colour Temperature	2700K-6500K	
CRI	≥85	
Beam Angle	120°	
Operating Temperature	{-20 to +60°C}	

Track LED Lights



Product Specification

Product Code	KL 35	KL 36
Input Power	20w	30w
Lumens	≥2000	≥3000
Input Voltage	85-280V AC 50Hz	
Power Factor	0.95	
Colour Temperature	2700K-6500K	
CRI	≥85	
Beam Angle	120°	
Operating Temperature	{-20 to +60°C}	

Nova T-Bulb



Product Specification

Product Code	KL 37	KL 38	KL 39
Input Power	10w	20w	30w
Lumens	≥100	≥200	≥300
Input Voltage	110-280V AC 50Hz		
Power Factor	0.95		
Colour Temperature	2700K-6500K		
CRI	≥85		
Operating Temperature	{-20 to +60°C}		

Aristo Plus Tube Lights



Product Specification

Product Code	KL 40	KL 41
Input Power	12w	20w
Outer Size	570mm	1130mm
Cutout Size	35mm	35mm
Height	20mm	20mm
Lumens/Watt	≥100	≥200
Input Voltage	110-280V AC 50Hz	
Power Factor	0.95	
Colour Temperature	2700K-6500K	
CRI	≥85	
Operating Temperature	{-20 to +60°C}	

Victor LED Bulb



Product Specification

Product Code	KL 42	KL 43	KL 44	KL 45	KL 46	KL 47	KL 48
Input Power	9w	12w	15w	20w	25w	36w	50w
Length/Dia	55mm	65mm	65mm	75mm	75mm	90mm	90mm
Height	100mm	120mm	120mm	135mm	135mm	180mm	180mm
Lumens/Watt	≥900	≥1200	≥1500	≥2000	≥2500	≥3600	≥5000
Beam Angle	180°						
Input Voltage	110-280V AC 50Hz						
Power Factor	≥0.95						
Colour Temperature	2700K-6500K						
CRI	≥85						

B-22

Venus AC-DC LED Bulb & Emergency Tubelight



Product Specification

Product Code	KL 49	KL 50	KL 51
Input Power	9w	15w	12w Emer. Tube Light
Height	50mm	50mm	570m
Length	120mm	120mm	35mm
Width	120mm	120mm	20mm
Shape	Standard	Standard	Standard
Cap Type	B22	B22	B22
Included Components	Battery Included	Battery Included	Battery Included
Lumens	≥900	≥1500	≥1200
Input Voltage	85-280V AC 50Hz		
Power Factor	0.95		
Colour Temperature	2700K-6500K		
CRI	≥85		
Beam Angle	120°		
Operating Temperature	{-20 to +60°C}		



Outdoor Lights

Outdoor surroundings are beautified by us for welcome gatherings,
 Now classy shapes adorn lights meant not only to enchant but to add elegance to occasions.

Flora Slim Flood Light



Product Specification

Product Code	KL 52	KL 53	KL 54	KL 55	KL 56	KL 57
Input Power	20w	30w	50w	100w	150w	200w
Dimension	195x170x60mm	195x170x60mm	235x200x67mm	285x250x70mm	345x310x80mm	430x330x180mm
Lumens	≥200	≥300	≥500	≥1000	≥1500	≥2000
CCT (K)	3000K,4000K,6000K					
Driver	Inbuilt					
Power Factor	>0.90					
CRI	≥0.80					
Beam Angle	60°					
Material	Aluminium Casting					
Operating Voltage	85-300 AC					
Over Volt. Shut Down	85-270 AC					
Surge Protection	Upto 5.5 KVA					

Maxx Plus LED Street Light



Product Specification

Product Code	KL 58	KL 59	KL 60	KL 61	KL 62
Input Power	20w	30w	50w	70w	100w
Dimension	325x110x55mm	385x150x60mm	395x190x65mm	395x190x65mm	475x240x90mm
Lumens	≥200	≥300	≥500	≥700	≥1000
CCT (K)	3000K,4000K,6000K				
Driver	Inbuilt				
Power Factor	>0.90				
CRI	≥0.80				
Beam Angle	120°				
Material	Aluminium Casting				
Operating Voltage	85-300 AC				
Over Volt. Shut Down	85-270 AC				
Surge Protection	Upto 5.5 KVA				

High Bay Light



Product Specification

Product Code	KL 63	KL 64	KL 65
Input Power	100w	150w	200w
Outer Dia	380mm	380mm	430mm
Depth	180mm	180mm	240mm
Lumens	≥ 1000	≥ 1500	≥ 2000
CCT (K)	3000K, 4000K, 6000K		
Power Factor	> 0.90		
CRI	≥ 0.80		
Material	Aluminium Casting		
Operating Voltage	85-300 AC		
Over Volt. Shut Down	85-270 AC		
Surge Protection	Upto 5.5 KVA		

Outdoor Garden Lights



Half K Light

Product Code KL 66
Watt 3W, 5W
Colour CW, NW, WW



Cylinder Light

Product Code KL 67
Watt 3W+3W, 5W+5W
Colour CW, NW, WW



Spike Light

Product Code KL 68
Watt 7W, 12W
Colour CW, NW, WW



Foot Light

Product Code KL 69
Watt 6W
Colour CW, NW, WW



K Light

Product Code KL 70
Watt 3W+3W, 5W+5W
Colour CW, NW, WW